						Bi Pod and			Slings	Drop of the	Drop of the
	Average		Overall	<u>Forend</u>	Right or Left	Pic Rail	<u>Tri-Pod</u>	QD Cup	<u>Studs</u>	Comb from	buttpad from
Stock Model	Weight	<u>LOP</u>	<u>Length</u>	<u>Width</u>	<u>Handed</u>	Compatible*	Compatible *	Compatible *	<u>Included</u>	<u>center bore</u>	<u>center bore</u>
AG Privateer	24 oz.	13.5	29.5"	1.15"	Yes	Yes	Yes	Yes	2	.625 inches	.325 inches
AG Sportsman	26 oz.	13.5	30.8"	1.75"	Right Only	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Carbon All Terrain (CAT)	26 oz.	13.5"	30.8"	1.75"	Yes	Yes	Yes	Yes	2	.625 inches	.375 inches
AG Visigoth	28 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.25 inches	.2 inches
AG Chalk Branch	31 oz.	13.5"	31"	2"	Yes	Yes	Yes	NO	3	.2 inches	.2 inches
AG Prairie Varmint	31 oz.	13.5"	30.9"	2 to 2.5"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Alpine Hunter	31 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Ferrata (Thumbhole)	34 oz.	13.5"	32.3"	1.75"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Gladius	34 oz.	13.5"	30.9"	2.375"	Yes	Yes	Yes	Yes	3	.2 inches	.2 inches
AG Adjustable Hunter	40 oz.	13.5"	30.9"	1.8"	Yes	Yes	Yes	Yes	3	.2 inches with cheek riser at lowest position	.2 inches

NOTE: Stocks that are finsihed with the Carbon Fiber exposed option can be 1 to 2 ounces lighter than the weights listed above.

## \* Customize your stock:

- 1) AG can add a 5" long, 1/4" thick aluminum insert into the forend of the stock. The end user or AG can drill and tap holes into this insert for additional swivel studs, bi-pod or picatinny rails.
- 2) AG can install an aluminum insert forward of the recoil lug to accommodate a tri-pod. This insert will be threaded for a 1/4 20 screw.
- 3) Stocks that have two slings swivels installed, the swivels are approximately 2.5" apart.